



Sun Control Window Films

Performance Results:

Visible Light Transmitted	24%
Total Solar Energy Rejected	66%
UV Light Rejected	99%
Glare Reduction	72%
Visible Light Reflected Interior	13%
Visible Light Reflected Exterior	29%
Solar Heat Reduction	59%



Night Vision 25

*Enhancing light
as only 3M can*



Night Vision 25 Benefits:

- Great heat rejection provides energy savings and improved comfort
- A warm natural hue invites warmth and beauty to any room
- Extends the life of furnishings by significantly reducing UV rays, the largest cause of fading
- Low interior and exterior reflectivity, especially at night!
- New 3M nano-technology enhances color stability
- Reduces glare and eye discomfort
- Comprehensive 3M manufacturer's warranty
- Increases personal safety from flying glass
- Superior scratch resistant coating



The Skin Cancer Foundation recommends this 3M Window Film product as an effective UV protectant.

Night Vision 25

*Enhancing light
as only 3M can*



Glass Type (All 1/4")	Single Pane Clear	Single Pane Tinted	Double Pane Clear	Double Pane Tinted
Visible Light Transmitted	24%	14%	22%	13%
Total Solar Energy Rejected	66%	67%	57%	67%
UV Light Rejected	99%	99%	99%	99%
Glare Reduction	72%	72%	71%	71%
Visible Light Reflected Int.	13%	13%	13%	13%
Visible Light Reflected Ext.	29%	12%	32%	15%
Shading Coefficient	0.39	0.33	0.50	0.37
Emissivity	0.72	0.72	0.72	0.72
U Value	1.05	1.05	0.47	0.47
Solar Heat Reduction	59%	48%	38%	32%



Building and Commercial Services Division

3M Center, Building 223-2S-24
St. Paul, MN 55144-1000

Printed in U.S.A. © 3M 2007 70-0709-0162-7 (174.5)ii

For color and appearance on our sample cards, no UV Protection or Abrasion Coating has been applied.