



Sun Control Window Films


Performance Results:

Visible Light Transmitted	19%
Total Solar Energy Rejected	77%
UV Light Rejected	99%
Glare Reduction	78%
Visible Light Reflected	58%
Solar Heat Reduction	72%



Silver P18

A higher standard



P18ARL



Silver P18 Benefits:

- High heat rejection provides energy savings and improved comfort
- Reduces fading and helps to protect furnishings
- Comprehensive 3M manufacturer's warranty
- Reduces glare and eye discomfort
- Increases personal safety from flying glass

Glass Type (All 1/4")	Single Pane Clear	Single Pane Tinted	Double Pane Clear	Double Pane Tinted
Visible Light Transmitted	19%	10%	17%	9%
Total Solar Energy Rejected	77%	74%	70%	76%
UV Light Rejected	99%	99%	99%	99%
Glare Reduction	78%	80%	78%	80%
Visible Light Reflected	58%	20%	55%	20%
Shading Coefficient	0.26	0.30	0.34	0.28
Emissivity	0.65	0.65	0.65	0.65
U Value	0.95	0.95	0.47	0.47
Solar Heat Reduction	72%	57%	58%	49%

3M Building and Commercial Services Division
 3M Center, Building 223-2S-24
 St. Paul, MN 55144-1000

Printed in U.S.A. © 3M 2007 70-0709-0173-4 (37.5)ii

For color and appearance on our sample cards, no UV Protection or Abrasion Coating has been applied.